



Element[®]
eco-friendly • efficient • energy

BATTERY CHARGER EiHF SERIES

The ELEMENT[®] iHF Series is a line of intelligent and high frequency industrial battery chargers that feature advanced power electronics technologies and microprocessor controls. The new line features state-of-the-art power electronics technologies, resulting in higher efficiencies, smaller size, and lower weight. The advanced on-board microprocessor controls incorporate programmable charging algorithms that can be tailored to meet the needs of various battery chemistries including Flooded, Gel, and AGM Lead-Acid batteries.



Advantages:

- Compact size and weight
- High performance and high efficiency
- Advanced programming capabilities

Applications:

- Industrial electric vehicles:
 - Electric forklift trucks
 - Electric ground support equipment (GSEs)
- Electric and hybrid electric vehicles

FEATURES & BENEFITS

- **High Efficiency Soft Switching Power Conversion Technology**
The ELEMENT[®] iHF chargers utilize state-of-the-art power electronics technologies including soft switching power conversion, which greatly improves efficiency and reduces electromagnetic interference (EMI). With soft switching, higher switching frequencies (75-100kHz) are utilized resulting in reduced unit size and weight.
- **Multi Voltage Capability**
The ELEMENT[®] iHF Series is a multi-voltage battery charger eliminating the need for multiple chargers in a facility or plant. Users can standardize on a single charger from a single source simplifying installation, operation, and maintenance. With its advanced user interface, the chargers are field programmable to fit any battery size.
- **Advanced Intelligence and Controls**
The ELEMENT[®] iHF chargers features state-of-the-art microprocessor controls and advanced user interfaces including an on-board Infra Red port. Using a PDA device (a Palm Pilot) along with user friendly Palm software, users can easily and fully program various charging parameters and select among the various charging sequences that best meet their specific battery needs.
- **Advanced User Interface with Remote Control Capability**
Equipped with an RS-232, an RS-485, an IR port, and an optional Ethernet port, ELEMENT[®] extends its programmability and monitoring features to remote hosts such as PCs, PDAs, PLCs, and servers.



Element
eco-friendly • efficient • energy

ELEMENT® iHF Series Product Matrix

Specifications	LMT06KW48150T	LMT10KW48250T	LMT10KW80120T
Nominal VA Ratings	48V / 150A	48V / 250A	80V / 120A
Input Specs.			
Voltage	480VAC, 3-phase +10% Delta Connection with Earth Ground		
Current	8.3A rms nominal / phase	13.8A rms nominal / phase	13.8A rms nominal / phase
Power Factor	0.96 (Active Power Factor Correction)		
Input Protection	Main power switch with 25A fuses		
Output Specs.			
Voltage	48V Nom. / 62.5V Max.	48V Nom. / 62.5V Max.	80V Nom. / 110V Max.
Current	150A Max.	250A Max.	120A Max.
Power	6 kW Max.	10 kW Max.	10 kW Max.
Pk-Pk Voltage Ripple	< 1%		
Efficiency (typical)	92% at Full Load		
Protection			
Input	Under Voltage Over Voltage		
Output	Over Current Over Voltage Over Temperature Battery Reverse Polarity Protection		
Operating Conditions			
Ambient Temperature	32 – 104°F (0 – 40°C)		
Humidity	10-90% RH non-condensing		
Interface			
Communication	Isolated RS-232 (Ethernet optional)		
µcontroller	LCD/Keypad, RS-232, IR with a PDA (Palm Pilot)		
Cooling	Forced air (fans)		
Mechanical			
Dimensions (WxDxH)	9.25" x 6.75" x 29.5"	19" x 8.5" x 28"	
Weight	50 lb	90 lb	
Output Cabling	1/0	2/0	
Output Connectors	SBX w/aux. contacts or Euro		
Auxiliary Contacts	Interface with a 5kΩ battery thermistor or Element SP+		
Certifications	UL and cUL Listed		

GNB Industrial Power

USA – Tel: 877.462.4636

Canada – Tel: 800.268.2698

www.gnb.com

GB4092 2011-10

GNB
INDUSTRIAL POWER
A Division of Exide Technologies