


Aerial Work Platforms

DPL™ Super Series™

Specifications



| Models | DPL-25S | | DPL-30S | | DPL-35S | |
|-----------------|-------------|--------|-------------|---------|-------------|---------|
| Measurements | US | Metric | US | Metric | US | Metric |
| Working height* | 31 ft 4 in | 9.70 m | 36 ft | 11.14 m | 40 ft 10 in | 12.62 m |
| Platform height | 25 ft 4 in | 7.70 m | 30 ft | 9.14 m | 34 ft 10 in | 10.62 m |
| Height - stowed | 6 ft 6 in | 1.98 m | 6 ft 6 in | 1.98 m | 6 ft 6 in | 1.98 m |
| Length - stowed | 6 ft 10 in | 2.08 m | 6 ft 10 in | 2.08 m | 6 ft 10 in | 2.08 m |
| Width | 2 ft 7.5 in | .80 m | 2 ft 7.5 in | .80 m | 2 ft 7.5 in | .80 m |

Productivity

| Lift capacity:ANSI/CSA/CE | 750 lbs | 340 kg | 750 lbs | 340 kg | 600 lbs | 272 kg |
|---------------------------|---------|--------|---------|--------|---------|--------|
|---------------------------|---------|--------|---------|--------|---------|--------|

ANSI/CSA

Outrigger footprint:

| | | | | | | |
|----------------------------|-------------|--------|------------|--------|------------|--------|
| A length | 7 ft 2 in | 2.11 m | 7 ft 6 in | 2.29 m | 7 ft 6 in | 2.29 m |
| B width | 4 ft 8.5 in | 1.44 m | 5 ft 8 in | 1.73 m | 5 ft 8 in | 1.73 m |
| C corner access | 1 ft 5 in | .43 m | 2 ft | .61 m | 2 ft | .61 m |
| D wall access front | 7 in | .18 m | 9 in | .23 m | 9 in | .23 m |
| E wall access side | 1 ft 4 in | .41 m | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m |

CE

Outrigger footprint:

| | | | | | | |
|----------------------------|-------------|--------|--------------|--------|--------------|--------|
| A length | 6 ft 10 in | 2.08 m | 7 ft 2.25 in | 2.19 m | 7 ft 2.25 in | 2.19 m |
| B width | 4 ft 8.5 in | 1.44 m | 5 ft 8.75 in | 1.75 m | 5 ft 8.75 in | 1.75 m |
| C corner access | 1 ft 5 in | .43 m | 2 ft | .61 m | 2 ft | .61 m |
| D wall access front | 7 in | .18 m | 9 in | .23 m | 9 in | .23 m |
| E wall access side | 1 ft 4 in | .41 m | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m |

| | | | | | | |
|-----------------|-------------|--------|-------------|--------|-------------|--------|
| Platform length | 6 ft | 1.83 m | 6 ft | 1.83 m | 6 ft | 1.83 m |
| Platform width | 2 ft 3.5 in | .70 m | 2 ft 3.5 in | .70 m | 2 ft 3.5 in | .70 m |

Power

| | |
|-------------------------|--------------------------------------|
| Power source: AC models | 110 V / 50-60 Hz or 220 V / 50-60 Hz |
| DC models | 12 V |

Weight**

| | | | | | | |
|---------------|-----------|--------|-----------|--------|-----------|--------|
| ANSI (AC)/CSA | 1,371 lbs | 622 kg | 1,474 lbs | 669 kg | 1,574 lbs | 714 kg |
| ANSI (DC)/CSA | 1,481 lbs | 672 kg | 1,584 lbs | 718 kg | 1,684 lbs | 764 kg |
| CE (AC) | 1,371 lbs | 622 kg | 1,474 lbs | 669 kg | 1,645 lbs | 746 kg |
| CE (DC) | 1,481 lbs | 672 kg | 1,584 lbs | 718 kg | 1,755 lbs | 796 kg |

Standards Compliance

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Weight will vary depending on options and/or country standards

Features

Standard Features

Measurements

DPL-25S

- 31 ft 4 in (9.55 m) working height
- 25 ft 4 in (7.72 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lbs (340 kg) lift capacity

DPL-30S

- 36 ft (10.97 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lbs (340 kg) lift capacity

DPL-35S

- 40 ft 10 in (12.62 m) working height
- 34 ft 10 in (10.62 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 600 lbs (272 kg) lift capacity

Productivity

- Large platform with room for 2 workers
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Patented outrigger interlock system
- Outrigger storage sockets
- Swivel-lock caster
- Tie down attachment points
- Forklift pocket access on all sides
- Angled entry ladder
- LED lights confirm proper set-up of outriggers
- Winch attachment points
- Locking key switch

Power

- DC models include a 15 amp charging system with 110V / 50-60 Hz or 220V / 50-60 Hz input voltage

Options & Accessories

Productivity

- Operational warning light and descent alarm package (mandatory for CE and AUS)
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

Platform

- 6ft x 2ft 3in (1.83 m x .69 m)

Power

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V 190 Amp battery



Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By: